EKOPRD X5



Environmentally neutral
and safe for soil and groundwater.

Recommended for:

- Fire rescue paths
- High frequented parking spaces
- Heavy load storage / areas
- etc...

SPECIFICATION	
Dimensions:	330 x 330 x 48 mm
Wall thickness:	3 mm
Dimensional stability:	-20° / + 60° C
Solubility:	resistant to acids, alkalis, alcohol, oil and petrol (de-icing salt, ammonia, acid rain, etc.)
Moisture absorption:	0,01 %
Weight per m²:	8,65 kg
Weight per piece:	0,961 kg
Interlock:	54 notched joints per m^2
Max. open surface:	approx. 80 %
Material:	PE - PP, recycled
Load-bearing capacity:	up to 75 t / m^2 (depending on fill type)
Compressive strenght:	up to 16 t point axle load (DIN 1072)
UV-resistant and weatherproof:	according to DIN EN ISO 4892-3 and DIN EN 438-2 19
Enviromental compatibility:	environmentally neutral
Heavy-duty:	48 mm
Tensile strenght:	> 5 kN/lfm
Package:	
Standard installation unit:	1 layer = 12 pieces, equates 1,33 m^2
Layer per pallet:	45
Area per pallet:	60 m^2
Qty. per pallet:	540 pieces
Dimensions:	1 350 x 1 050 x 2 350 mm
Weight per pallet:	545 kg

TÜV NORD
TÜV NORD CERT GmbH
Made in Germany

NOTES:

a.) Please note the installation instructon on our website !
Subject to change without prior E. & O.E.
b.) The listed details are nominal dimensions and subject to a certain tolerance due to material changes.

www.ekoprd.eu info@ekoprd.eu